

EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER : 06180336
PUBLICATION DATE : 28-06-94


APPLICATION DATE : 14-12-92
APPLICATION NUMBER : 04353585

APPLICANT : NIPPONDENSO CO LTD;

INVENTOR : NONOYAMA HAYASHI;

INT.CL. : G01R 27/26 G01D 5/24 G01L 1/14
G01L 9/12

TITLE : CAPACITANCE TYPE PHYSICAL
QUANTITY DETECTING DEVICE



ABSTRACT : PURPOSE: To suppress voltage fluctuation across counterposed electrodes and prevent the electrodes from coming contact with each other so as to easily make a sensor more precise by detecting the capacitance change of a capacitance sensor under a low applied-voltage condition by using an operational amplifier.

CONSTITUTION: Resistors R_1 and R_2 are respectively connected between an input terminal 1 and the inverted input terminal of an operational amplifier 8 and between the inverted input terminal and an output terminal 3. In addition, a capacitance sensor 6 and switch 7 are respectively connected between the terminal 1 and the non-inverted input terminal of the amplifier 8 and between the non-inverted input terminal and a common terminal 2. By closing the switch 7, the sensor 6 is charged with a voltage V_{in} and, at the same time, a physical quantity to be measured, for example, reference acceleration is impressed upon the sensor 6. When a physical quantity to be measured, for example, acceleration is impressed upon the sensor 6 and the capacitance value of the sensor 6 becomes C_1 , the voltage variation $\Delta V = V_{in} - V_{out}$ of the sensor 6 becomes $\Delta V = (1 + (R_2/R_1)) \cdot (\Delta C/C_1) \cdot V_{in}$. Therefore, when the resistance values of the resistors R_1 and R_2 are appropriately set, the variation $\Delta C/C_1$ of the capacitance can be largely amplified with a small voltage change V .

COPYRIGHT: (C) JPO